



DZMD-600 (6/12/18 detection zones) arched walkthrough metal detector, WTMD, DFMD, doorframe metal detector gate



Working environment:

- A. environment temperature: -20 to 45 °C (non-condensing)
- B. Storage Temperature: -20 to +60 °C (non-condensing)
- C. Humidity: 20% to 95%
- D. the installation site as far as possible from power line and communication cable
- E. door around 2 meters there should be no large pieces of metal and a strong magnetic field
- F. suitable for indoor use, if indeed you installed in the outdoor, should be attached to the canopy such as rain and sun protection facilities

Technical characteristics

- A. module of the application and various settings are used in digital signal control
- B. according to the sample automatically adjust the sensitivity.



- with LED on both sides of the diffusion alarm mode, it can distinguish metal size
- D. the strength of the indicator can automatically check the magnetic field around the environment
- E. 7-inch large LCD color screen, and graphic operation interface

Technical parameters

Input power supply: AC85~264V/50Hz.

Standby power consumption: $\leq 10W$, ultra-low power consumption, low radiation.

Frequency: 100-band, power adaptation.

Working environment: $-20^{\circ}C$ — $+45^{\circ}C$.

System detection: when turned on, detecting whether the system is faulty.

Partition function: 6/12/18 detection areas can be freely divided, to accurately determine the metal items of the location.

To adjust the sensitivity range: the sensitivity of both 1000-level adjustable, 0-999 level

Alarm function: sound and light alarm at the same time, and can record the alarm number 99999 times

Alarm query: can be according to the date and time to search the alarm recording and the indicator display each alarm location information

Anti-interference: digital circuit design, leak-proof packet, the infrared anti-interference, anti-external interference ability.

The application of occasions: high school, low sensitivity to adapt to all the security options and quick debugging.

Back-up power supply (option function) : the battery power is not less than 8 hours.

Sensitivity adaptive: according to the human body comes with metal through the security gate to identify the sensitivity

Identifying features: use LED lights on both sides of the diffusion display mode to inform the security personnel metal items size.

Fixed ID: each product has a fixed ID number.

Multi-language display: you can select the appropriate language according to need.

Million years calendar: displays year, month, day, hour, min.

Manage encryption: to prevent data from being illegally modified or misuse causes the product to work abnormally